



HEAVY SADDLE



FEATURES AND BENEFITS.

| | |
|----------------------|---|
| Description:- | <ul style="list-style-type: none"> * For mounting plain or insulated pipes * Corner locking and better gripping of electrical conduits. * Easy to install because of light weight * Maximum temperature : 343°C (650°F) |
| Material:- | Steel, other materials on request |
| Special:- | <ul style="list-style-type: none"> * Electro galvanized as per ASTM B 633 * Designed to meet MSS Standard SP-58, type 26 and SP-69. |

| Product Code | Nominal Pipe Size | | Pipe OD(D) mm | Hole Size(S) mm | Max Load (N) | Microns (μ) | Box Quantity |
|--------------|-------------------|-------|------------------|--------------------|-----------------|----------------|-----------------|
| | In. | mm | | | | | |
| HGEPUC027 | ¾" | DN20 | 26.7 | M6 | 1250 | 8 -15 | 1200 |
| HGEPUC034 | 1" | DN25 | 33.4 | M6 | 1250 | 8 -15 | 1000 |
| HGEPUC042 | 1 ¼" | DN32 | 42.1 | M6 | 1250 | 8 -15 | 1000 |
| HGEPUC048 | 1 ½" | DN40 | 48.2 | M6 | 1250 | 8 -15 | 800 |
| HGEPUC060 | 2" | DN50 | 60.3 | M6 | 1250 | 8 -15 | 750 |
| HGEPUC073 | 2 ½" | DN65 | 73 | M6 | 1250 | 8 -15 | 700 |
| HGEPUC090 | 3" | DN80 | 88.9 | M6 | 1250 | 8 -15 | 600 |
| HGEPUC114 | 4" | DN100 | 114.3 | M6 | 1250 | 8 -15 | 500 |
| HGEPUC141 | 5" | DN125 | 141.3 | M6 | 1250 | 8 -15 | 400 |
| HGEPUC168 | 6" | DN150 | 168.3 | M6 | 1250 | 8 -15 | 250 |

NOTE:- 1. OTHER DIMENSIONS AVAILABLE ON REQUEST.

