



## LIGHT SADDLE



### FEATURES AND BENEFITS.

<b>Description:-</b>	<ul style="list-style-type: none"> <li>* It is recommended for supporting a piping system with vertically or horizontally to walls or ceilings.</li> <li>* Easy to install because of light weight.</li> <li>* Maximum temperature : 343°C (650°F).</li> </ul>
<b>Material:-</b>	Steel, other materials on request.
<b>Special:-</b>	<ul style="list-style-type: none"> <li>* Electro galvanized as per ASTM B 633.</li> <li>* Designed to meet MSS Standard SP-58, type 26 and SP-69.</li> </ul>

Product Code	Nominal Pipe Size In.	mm	Pipe OD (D) mm	Hole Size (S) mm	Max Load (N)	Microns (μ)	Box Quantity
HGEPLS022	½"	DN15	21.3	M6.2	500	8 -15	2000
HGEPLS027	¾"	DN20	26.7	M6.2	500	8 -15	1750
HGEPLS034	1"	DN25	33.4	M6.2	500	8 -15	1500
HGEPLS042	1 ¼"	DN32	42.1	M6.2	500	8 -15	1250
HGEPLS048	1 ½"	DN40	48.2	M6.2	500	8 -15	1000
HGEPLS060	2"	DN50	60.3	M6.2	500	8 -15	800
HGEPLS073	2 ½"	DN65	73	M6.2	500	8 -15	750
HGEPLS090	3"	DN80	88.9	M6.2	500	8 -15	500
HGEPLS114	4"	DN100	114.3	M6.2	500	8 -15	300

NOTE:- 1. OTHER DIMENSIONS AVAILABLE ON REQUEST.

