



## HALF SADDLE



### FEATURES AND BENEFITS.

<b>Description:-</b>	<ul style="list-style-type: none"> <li>* Recommended for support of standard conduit, cable and steel pipe on walls or sides of beams.</li> <li>* Not recommended for use horizontally on ceilings, bottoms safety of beams and similar installations since the factor of is greatly reduced when so used.</li> <li>* Maximum temperature : 343°C (650°F).</li> </ul>
<b>Material:-</b>	Steel, other materials on request.
<b>Special:-</b>	<ul style="list-style-type: none"> <li>* Electro galvanized as per ASTM B 633.</li> <li>* Designed to meet MSS Standard SP-58, type 26 and SP-69.</li> </ul>

Product Code	Nominal Pipe Size		Pipe OD(D) mm	Hole Size(S) mm	Max Load (N)	Microns (μ)	Box Quantity
	In.	mm					
HGEPHS022	½"	DN15	21.3	M6.2	1250	8 -15	2000
HGEPHS027	¾"	DN20	26.7	M6.2	1250	8 -15	1600
HGEPHS034	1"	DN25	33.4	M6.2	1250	8 -15	1200
HGEPHS042	1 ¼"	DN32	42.1	M6.2	1250	8 -15	1000
HGEPHS048	1 ½"	DN40	48.2	M6.2	1250	8 -15	800
HGEPHS060	2"	DN50	60.3	M6.2	1250	8 -15	600

NOTE:- 1. OTHER DIMENSIONS AVAILABLE ON REQUEST.

