

HEX BOLT (DIN 933)

FEATURES AND BENEFITS.					
Description:-	 * Hex bolts can be used for many different applications that include fastening wood, steel, and other construction materials for projects such as docks, bridges, highway structures, and buildings. * Hex bolts with forged heads are also commonly used as headed anchor bolts. 				
Material:-	Mild Steel, Carbon Steel, Alloy Steel & Stainless Steel.				
Standards:-	ASTM/ ASME/ DIN/ BS EN ISO / JIS				
Threads:-	UNC, 8UN, UNF, Metric Coarse and Metric Fine.				
Size Range:-	M6 to M64 in Metric series.				
	¼" to 2½" in Imperial				
	Bigger sizes can be manufactured as per order.				

....

* Typical Grades & Standards :-

-BS3692 / BS4190 grade 4.6, 4.8, 5.6, 5.8, 8.8, 10.9 and 12.9 -ASTM A307 Grade A and B -ASTM A325 -ASTM A193 Grade B7, B7M, B8, B8M & B16 -ASTM A320 Grade L7 & L7M -Stainless Steel 304, 304L, 316, 316L, A2-70/ 80, A4-70/ 80 * Offering Information :-

-Dimensions – Size Dia and Length.

-Standards and Grade

- -Finish (Black, GI, Yellow, HDG, Cadmium, Nickel, PTFE etc)
- -Nut and washer quantity

Product Code	Size (d1)	S (mm)	e (mm)	k (mm)	a (mm)
HGEPHB03	M3	5.5	6.01	2	1.5
HGEPHB04	M4	7	7.66	2.8	2.1
HGEPHB05	M5	8	8.79	3.5	2.4
HGEPHB06	M6	10	11.05	4	3
HGEPHB08	M8	13	14.38	5.3	3.75
HGEPHB10	M10	17	18.9	6.4	4.5
HGEPHB12	M12	19	21.1	7.5	5.25
HGEPHB14	M14	22	24.49	8.8	6
HGEPHB16	M16	24	26.75	10	6
HGEPHB18	M18	27	30.14	11.5	7.5
HGEPHB20	M20	30	33.53	12.5	7.5
HGEPHB22	M22	32	35.72	14	7.5
HGEPHB24	M24	36	39.98	15	9
HGEPHB27	M27	41	45.2	17	9
HGEPHB30	M30	46	50.85	18.7	10.5
HGEPHB33	M33	50	55.37	21	10.5
HGEPHB36	M36	55	60.79	22.5	12
HGEPHB39	M39	60	66.44	25	12
HGEPHB42	M42	65	71.3	26	13.5
HGEPHB45	M45	69	76.95	28	13.5
HGEPHB48	M48	75	82.6	30	15
HGEPHB52	M52	80	88.25	33.5	15

NOTE:- 1. OTHER DIMENSIONS AVAILABLE ON REQUEST.

2. OTHER FINISH ALSO AVAILABLE ON REQUEST.

